

Sliding, Pocket & Barn Door Locks



PD9500	PD8000	BD4000
PD9600	PD5000	BD1000
PD3000	PD2000	WS90/WS90L

CONTENTS

Page 02	PD9500 Mortise Lock for Sliding Doors with Emergency Egress
Page 03	PD9500 Components and Dimensions
Page 04	PD9500 Functions
Page 05	PD9600 Self-latching Mortise Lock for Sliding Doors
Page 06	PD9600 Features
Page 07	PD9600 Components and Dimensions
Page 08	PD9600 Functions
Page 10	PD9500 & PD9600 Rose and Lever Designs
Page 11	PD9500 & PD9600 Thumbturn Options
Page 12	PD9500 & PD9600 Faceplate and Strike
Page 13	PD9500 Series How to Order
Page 14	PD9600 Series How to Order
Page 15	PD3000 Narrow Profile ICU Lock for Sliding Doors
Page 16	PD3000 Components and Dimensions
Page 18	PD8000 Mortise Lock for Sliding or Pocket Doors
Page 19	PD8000 Components and Dimensions
Page 20	PD8000 Functions
Page 21	PD5000 Mortise Lock for Sliding or Pocket Doors
Page 22	PD5000 Components and Dimensions
Page 23	PD5000 Functions
Page 24	Thumbturn Options for PD5000 & PD8000
Page 27	FH17 Bezel Flush Pull
Page 28	FH27/FH27SL Linear Flush Pull
Page 29	FH29 Arc Flush Pull
Page 30	FH31 Regal Flush Pull
Page 31	FH32 Crown Flush Pull
Page 32	FH22 Luna Flush Pull
Page 33	FH22CF Luna Concealed Fixing Flush Pulls
Page 34	FH23 Urban Flush Pull
Page 35	FH23CF Urban Concealed Fixing Flush Pulls
Page 36	PD2000 Twistlock Edge Pull Privacy Lock
Page 37	PD8000/PD5000 Faceplate and Strike
Page 40	PD8000 How to Order
Page 41	PD5000 How to Order
Page 43	PD2000 How to Order
Page 45	BD4000 Concealed Jamb Mount Barn Door Privacy Lock
Page 47	BD4000 Flush Trim Barn Door Privacy Lock
Page 48	BD4000 Concealed Jamb Mount for Metal Studs Barn Door Privacy Lock
Page 49	BD4000 Privacy Lock Trim Options
Page 50	BD4000 How to Order
Page 51	BD1000 Surface Mount Barn Door Privacy Lock
Page 52	WS90 Wall Strike for Lockable Barn Doors
Page 53	WS90L Large Wall Strike for Lockable Barn Doors
Page 55	ADA Surface Pulls
Page 56	ADA Pull Options
Page 58	Mortise Cylinders and Keys

Disclaimer: All information in this catalog has been deemed accurate as of the date of printing. We are continuously improving and expanding our line in an effort to offer our clients the finest quality products and services; therefore, Unison Hardware, Inc., reserves the right to alter this information or correct printing errors at any time.

©2023 Unison Hardware, Inc. All Rights Reserved. V20260410

PD9500, PD9600 & PD3000 MORTISE LOCKS for Sliding Doors



PD9500 with XGS205 Frankfurt



PD9600 with XGT243 Sunrise



PD3000 with NE502 Munich

PD9500 MORTISE LOCK

for Sliding Doors with Emergency Egress



SPECIFICATIONS

Door Thickness	1-3/4" (45mm) Standard 1-3/8" (35mm) Thin Door Kit available for XGT only 2" to 2-1/4" (50mm to 57mm) Thick Door Kit available
Backset	2-3/4" (70mm) 2-1/2" (63.5mm)
Lever Spindle	8 x 8mm square
Thumbturn Spindle	5 x 5mm square
Center to Center Distance	Lever to Cylinder: 3-7/8" (98mm) Lever to Thumbturn: 2-11/16" (68mm)
Cylinder	Schlage C keyway 6 pin, 1-1/4" mortise cylinder with 2 keys (standard). Optional SFIC and LFIC housing and cores available
CAM	CAM01-SCL Clover Cam
Material	Trim: Stainless Steel Lockcase: Heavy Gauge Steel Bolt: Brass and Stainless Steel Faceplate/Strike: Stainless Steel Cylinder: Solid Brass

FEATURES

- Form meets function with 12 designer trims, five function options, and a variety of available finishes
- Patented anti-binding winged deadbolt provides smooth operation for safety and security
- Single-action deadbolt release for emergency egress
- Adjustable strike aids door and frame alignment for easier installation
- ADA compliant trim

CODE COMPLIANCE


- ANSI/BHMA A156.36 Auxiliary Locks
- ANSI/BHMA A156.18 Finishes
- ANSI A117.1 ADA Accessibility

STANDARD FINISHES

- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- PVD4 Satin Brass (243, 267 and 321 Lever Design)
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze

For additional finish options not listed, contact Sales Department for MOQ and lead times


PD9500 COMPONENTS AND DIMENSIONS



Description


- 1 Lockcase and faceplate; 2-3/4" backset or 2-1/2" backset
- 2 1" (25.4mm) heavy-duty brass bolt throw with self-retracting non-marring hooks
- 3 ADA Compliant thumbturn
- 4 Heavy-duty Stainless Steel cast rose with choice of X Series lever design
- 5 Schlage C keyway, 6 pin 1-1/4" mortise cylinder
- 6 Adjustable strike for deadbolt; up to 1/4" vertical adjustability (6.35mm)

PD9500 FUNCTIONS




Privacy: PD9540

- Deadbolt can be retracted by inside lever or outside emergency coin release
- Thumbturn inside locks and unlocks deadbolt
- Outside lever is rigid at all times
- Inside lever can always retract deadbolt for emergency egress




Classroom: PD9570

- Deadbolt can be locked or unlocked by outside key
- No thumbturn on inside
- Outside lever is rigid at all times
- Inside lever can always retract deadbolt for emergency egress




Entry/Office : PD9550

- Deadbolt can be retracted or engaged by inside thumbturn or outside key
- Outside lever is rigid at all times
- Inside lever can always retract deadbolt for emergency egress



Security Communicating: PD9595

- Keyed function provides security for connected rooms; only an authorized user (e.g., hotel staff) can lock/unlock with key
- Unlocking deadbolt with key allows door to be opened from lever side
- Lever is always rigid
- No lever on opposite side from cylinder; blank or blind rosette only



Patio: PD9560

- Inside thumbturn locks or unlocks deadbolt
- Outside lever is rigid at all times
- No keyed cylinder outside; door cannot be opened from outside when locked
- Inside lever can always retract deadbolt for emergency egress

PD9600 SELF-LATCHING MORTISE LOCK

for Sliding Doors



SPECIFICATIONS

Door Thickness	1-3/4" (45mm) Standard 1-3/8" (35mm) Thin Door Kit available for XGT only 2" to 2-1/4" (50mm to 57mm) Thick Door Kit available
Backset	2-3/4" (70mm) 2-1/2" (63.5mm)
Lever Spindle	8 x 8mm square
Thumbturn Spindle	5 x 5mm square
Center to Center Distance	Lever to Cylinder: 3-7/8" (98mm) Lever to Thumbturn: 2-11/16" (68mm)
Cylinder	Schlage C keyway 6 pin, 1-1/4" mortise cylinder with 2 keys (standard). Optional SFIC and LFIC housing and cores available
CAM	CAM01-SCL Clover Cam (Use of an incorrect cylinder cam may result in improper lock operation and failure of the locking or unlocking functions)
Material	Trim: Stainless Steel Lockcase: Heavy Gauge Steel Bolt: Brass and Stainless Steel Faceplate/Strike: Stainless Steel Cylinder: Solid Brass

FEATURES

- Dynamic locking solutions for all major functions of commercial openings, plus designer trim and a variety of available finishes
- Built-in mechanical self-latching or self-locking
- Meets and exceeds ANSI/BHMA 156.36 standard
- Emergency Egress via inside lever
- ADA Compliant trim



CODE COMPLIANCE


- UL1784 Standard for Safety Air Leakage test of Door Assemblies and Openings
- ANSI/BHMA A156.18 Finishes
- ANSI A117.1 ADA Accessibility

STANDARD FINISHES

- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- PVD4 Satin Brass (243, 267 and 321 Lever Design)
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze


For additional finish options not listed, contact Sales Department for MOQ and lead times

PD9600 FEATURES




Self-latching / Self-locking

- Self-latching: When sliding door is closed, deadbolt is automatically engaged into strike. Lever retracts deadbolt to unlatch
- Self-locking: When sliding door is closed, deadbolt is automatically engaged into strike. Outside lever is in locked position, keeping door locked from outside. Key or inside thumbturn unlocks outside lever and unlocks deadbolt
- Inside lever always allows emergency egress



Actuator

- Extended release button is built onto the faceplate of the lock
- Once door is closed, the release button is activated, which triggers the deadbolt into the strike




X Series Trim

- Heavy-duty wire torsion spring
- Cast stainless steel sub-rose with knurled brass nut for mechanical integrity and strength



ADA Accessibility


- ADA Compliant trim



Emergency Egress

- Single action emergency egress for life safety and code compliance


PD9600 COMPONENTS AND DIMENSIONS



Description


- 1 Lockcase and faceplate; 2-3/4" backset or 2-1/2" backset
- 2 1" (25.4mm) heavy-duty brass bolt throw with self-retracting non-marring hooks
- 3 ADA Compliant thumbturn
- 4 Heavy-duty Stainless Steel cast rose with choice of X Series lever design
- 5 Schlage C keyway, 6 pin 1-1/4" mortise cylinder
- 6 Adjustable strike for deadbolt; up to 1/4" vertical adjustability (6.35mm)

PD9600 FUNCTIONS




Passage: PD9610

- Actuator button on faceplate contacts strike and automatically engages deadbolt when sliding door closes
- No thumbturn or keyed cylinder
- Outside and inside levers are active and can retract deadbolt




Privacy: PD9640

- Actuator button on faceplate contacts strike and automatically engages deadbolt when sliding door closes
- Outside lever is rigid when locked and cannot retract deadbolt
- Outside lever can retract deadbolt when unlocked
- Inside thumbturn can lock or unlock outside lever
- Outside coin turn emergency release can also unlock outside lever
- Operating inside lever to retract deadbolt **simultaneously** resets outside lever and inside thumbturn to unlocked position
- Inside lever can always retract deadbolt for emergency egress




Inner Entry: PD9650

- Actuator button on faceplate contacts strike and automatically engages deadbolt when sliding door closes
- Outside lever locked or unlocked by key or inside thumbturn
- Outside lever is rigid when locked and cannot retract deadbolt
- Outside lever retracts deadbolt when unlocked
- Operating inside lever for egress **simultaneously** resets outside lever and inside thumbturn to unlocked position
- Inside lever can always retract deadbolt for emergency egress



Entrance: PD9653


- Actuator button on faceplate contacts strike and automatically engages deadbolt when sliding door closes
- Outside lever locked or unlocked by key or inside thumbturn
- Outside lever is rigid when locked and cannot retract deadbolt
- Outside lever retracts deadbolt when unlocked
- Outside lever will remain in locked or unlocked position until user resets status with key or inside thumbturn
- Operating inside lever will **not** change the locked or unlocked status of the outside lever or inside thumbturn
- Inside lever can always retract deadbolt for emergency egress



Patio: PD9660


- Actuator button on faceplate contacts strike and automatically engages deadbolt when sliding door closes
- Outside lever is locked or unlocked by inside thumbturn
- Outside lever is rigid when locked and cannot retract deadbolt
- Outside lever can retract deadbolt when unlocked
- No keyed cylinder outside; door cannot be opened from outside when locked
- Operating inside lever to retract deadbolt **simultaneously** resets outside lever and inside thumbturn to unlocked position
- Inside lever can always retract deadbolt for emergency egress

PD9600 FUNCTIONS




Classroom: PD9670

- Actuator button on faceplate contacts strike and automatically engages deadbolt when sliding door closes
- Outside lever is locked or unlocked only by key
- Outside lever is rigid when locked and cannot retract deadbolt
- Outside lever retracts deadbolt when unlocked
- No thumbturn on inside
- Operating inside lever for egress will **not** change the locked or unlocked status of outside lever
- Inside lever can always retract deadbolt for emergency egress




Storeroom: PD9680

- Actuator button on faceplate contacts strike and automatically engages deadbolt when sliding door closes
- Outside lever is locked or unlocked only by key
- Outside lever is rigid when locked and cannot retract deadbolt
- Outside lever retracts deadbolt when unlocked
- Key cannot be removed from cylinder when outside lever is unlocked; key can only be removed when outside lever is in locked position. Requires special CAM
- No thumbturn on inside
- Operating inside lever will **not** change locked status of outside lever
- Inside lever can always retract deadbolt for emergency egress




Exit: PD9690

- Actuator button on faceplate contacts strike and automatically engages deadbolt when sliding door closes
- Outside lever is always rigid and locked and cannot retract deadbolt
- No cylinder outside, no thumbturn inside
- Inside lever can always retract deadbolt for emergency egress



Communicating: PD9692


- Actuator button on faceplate contacts strike and automatically engages deadbolt when sliding door closes
- Lever retracts deadbolt
- No lever on opposite side, blank or blind rosette only



Security Communicating: PD9695

- Keyed function for connected rooms with security; only an authorized user may lock/unlock the room-side lever, e.g. hotel staff
- Actuator button on faceplate contacts strike and automatically engages deadbolt when sliding door closes
- Room-side lever is locked or unlocked by key
- Room-side lever can retract deadbolt when unlocked
- Room-side lever is rigid when key locks the lever
- No lever on opposite side; blank or blind rosette only

PD9500 & PD9600 ROSE AND LEVER DESIGNS



XGT Rose



XGS Rose



201 Cologne



202 Munich*



205 Frankfurt



221 Aurora



243 Sunrise



244 Twilight*



276 Plaza



318 Café



319 Hampton



320 Empire



321 Valencia*



345 Tokyo




346 Osaka*

All levers available in 32, 32D or CeraMax C19G, C19, CGY, or CDB
PVD4 finish available in the 243, 276, and 321 lever designs


*Return-to-Door Lever Designs: Complies with California and other state building codes for door openings

PD9500 & PD9600 THUMBTURN OPTIONS




EC-R530PVS-ADA (GT)

TT07 Thumbturn with coin release




EC-R530PVS (GT)

TT04 Thumbturn with coin release




EC-R530PVS-TT02 (GT)

TT02 Thumbturn with coin release




EC-S530PVS-ADA (GS)

TT07 Thumbturn with coin release




EC-S530PVS (GS)

TT04 Thumbturn with coin release




EC-S530PVS-TT02 (GS)

TT02 Thumbturn with coin release




EC-R530PVSW-ADA (GT)

TT07 Thumbturn with coin turn release and indicator




EC-R530PVSW (GT)

TT04 Thumbturn with coin turn release and indicator




EC-R530PVSW-TT02 (GT)

TT02 Thumbturn with coin turn release and indicator




EC-S530PVSW-ADA (GS)

TT07 Thumbturn with coin turn release and indicator



EC-S530PVSW (GS)


TT04 Thumbturn with coin turn release and indicator



EC-S530PVSW-TT02 (GS)


TT02 Thumbturn with coin turn release and indicator

PD9600 THUMBTURN OPTIONS




EC-R560TT07PVSW-ADA (GT)

TT07 Thumbturn with coin turn release and indicator



EC-R560TT04PVSW (GT)

TT04 Thumbturn with coin turn release and indicator




EC-R560TT02PVSW (GT)

TT02 Thumbturn with coin turn release and indicator

PD9500 FACEPLATE AND STRIKE



PD-83-FP (Standard 1" Faceplate)
PD-83-FP114 (Optional 1-1/4" Faceplate)




PD-ADJ-3D-STRK-FINISH (Strike and Dustbox Only)

PD9600 FACEPLATE AND STRIKE



PD-96-FP (Standard 1" Faceplate)
PD-96-FP114 (Optional 1-1/4" Faceplate)




PD-ADJ-3D-STRK-FINISH (Strike and Dustbox Only)

*The gap between the lock face and strike should not exceed 1/16" to ensure proper engagement of the self-latching/self-locking actuator.

SLIDING DOOR HANDING

Handing refers to the direction the door slides open. Example: If the door slides to the left to open, it is a left-handed door. Handing is determined from the exterior or key side of the door when facing into the room.



HOW TO ORDER

PD9500 Mortise Locks with X Series Levers for Sliding Doors

To order locksets, please describe the additional requirements in the same sequence as below. Please see price book for parts or additional service upcharge.

Rose	Lever	Lock	Function	Backset	Cylinder	Thumbturn	Indicator	Finish	Handing
XGS 1	201 2	-PD95 3	50 4	A 5	6	-GS07 7	8	-32D 9	-LH 10
ROSE	LEVER	LOCK	FUNCTION						
 XGT	 201	 -PD95	40 Privacy						
 XGS	 202	 205	50 Office / Entry						
	 221	 243	60 Patio						
	 244	 276	70 Classroom						
	 318	 319	95 Security Communicating						
	 320								
	 321	 345							
	 346								
			5 BACKSET						
			Backset Blank = 2-3/4"						
			Backset A = 2-1/2"						
			6 CYLINDER AND HOUSING (includes collar)						

LC = Less Cylinder



Blank = Standard Mortise 1-1/4" Cylinder



-S6 = Small Format Interchangeable Cylinder (SFIC) Housing 1-1/4", 6-Pin, Less Core, L Clover Cam

-S7 = Small Format Interchangeable Cylinder (SFIC) Housing 1-3/8", 7-Pin, Less Core, L Clover Cam

-L6 = Large Format Interchangeable Cylinder (LFIC) Housing 1-1/2", 6-Pin, Less Core, L Clover Cam



Order IC Cores and Thick Door Kits (TDKs) separately

7 THUMBTURN



GT02



GT04



Blank = GT07



GS02



GS04



GS07


8 INDICATOR

Blank = Without Indicator


-W = With Indicator

9 FINISH

Standard:



-32D




-C19G



-C19



-CGY



-CDB



-32



-PVD4

PVD4 finish available in the 243, 276, and 321 lever designs

10 HANDING

-RH = Right Hand

-LH = Left Hand

HOW TO ORDER

PD9600 Mortise Locks with X Series Levers for Sliding Doors

To order locksets, please describe the additional requirements in the same sequence as below. Please see price book for parts or additional service upcharge.

Rose	Lever	Lock	Function	Backset	Cylinder	Thumbturn	Indicator	Finish	Handing
XGT 1	243 2	-PD96 3	53 4	A 5	-S6 6	-GT4 7	-W 8	-32D 9	-LH 10
ROSE	LEVER	LOCK		FUNCTION					
 XGT	 XGS	 -PD96		10 Passage 40 Privacy 50 Inner Entry 53 Entrance 60 Patio 70 Classroom 80 Storeroom 90 Exit 92 Communicating 95 Security Communicating					
	201	202	205	221	243				
	244	276	318	319	320				
	321	345	346						

5 BACKSET

Backset Blank = 2-3/4"

Backset A = 2-1/2"

6 CYLINDER AND HOUSING (includes collar)

LC = Less Cylinder



Blank = Standard Mortise 1-1/4" Cylinder



-S6 = Small Format Interchangeable Cylinder (SFIC) Housing 1-1/4", 6-Pin, Less Core, L Clover Cam

-S7 = Small Format Interchangeable Cylinder (SFIC) Housing 1-3/8", 7-Pin, Less Core, L Clover Cam

-L6 = Large Format Interchangeable Cylinder (LFIC) Housing 1-1/2", 6-Pin, Less Core, L Clover Cam



Order IC Cores and Thick Door Kits (TDKs) separately

7 THUMBTURN



GT02



GT04



Blank = GT07



GS02



GS04



GS07

8 INDICATOR

Blank = Without Indicator

-W = With Indicator

9 FINISH

Standard:



-32D



-C19G



-C19



-CGY



-CDB



-32



-PVD4

PVD4 finish available in the 243, 276, and 321 lever designs

10 HANDING

-RH = Right Hand

-LH = Left Hand

PD3000 NARROW PROFILE ICU LOCK

For Sliding Doors



SPECIFICATIONS


Door Thickness	1-3/4" (45mm) Thick Door Kits available
Backset	1-1/4" (31.5mm)
Lever Spindle	8mm x 8mm square
Case Size	4-1/2" x 5/8" x 1-19/32" (114mm x 16mm x 40.5mm)
Handing	Non-Handed

Material	Narrow Escutcheon: Zinc Alloy Lever: Stainless Steel Lockcase: Stainless Steel Hook Bolt: Stainless Steel Faceplate/Strike: Stainless Steel
-----------------	---

FEATURES

- Narrow-profile mortise lock fits door openings where larger mortise locks cannot, including glass doors
- Stainless steel bolt, hub, and faceplate integrated in an innovative design with activator that provides self-latching function
- Designed to replace existing narrow profile locks; INOX retrofit is easy and provides improved strength, resilience, and durability
- Successfully tested to 250,000 cycles for lever and self-latching Hook Bolt

FUNCTION



Passage: PD3010



- Self-latching: When sliding door is closed, Hook Bolt is automatically engaged into strike
- Outside and inside levers are always unlocked and retract the Hook Bolt

STANDARD FINISHES

- 32D Satin Stainless Steel
- 19G Graphite Black
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze


For additional finish options not listed, contact Sales Department for MOQ and lead times

PD3000 COMPONENTS AND DIMENSIONS




DESCRIPTION


1. PD3000 lockcase
2. Self-Latching Hook Bolt
3. Narrow Escutcheon (NE) with 502 Munich lever
4. Actuator button to activate the retracted Self-Latching Hook Bolt
5. Strike



NOTE: Mortise lock can be installed with the actuator button in either the top or bottom position simply by turning the lock body when installing so that the hook direction is reversed. Ensure that the levers and strike are installed accordingly so that the door latches properly.



ESCUTCHEON DIMENSIONS



HOW TO ORDER

Specify the Escutcheon, Lever, Lock, Function, and Finish using the product identification below:

Standard Product Identifications

NE	502	-PD30	10	-32D	
					Finish
					Function Code
					Lockcase
					Munich Lever
					Escutcheon

PD8000 & PD5000 MORTISE LOCKS

with Surface Pulls for Sliding Doors



PD8000 with PHIX41714 ADA Pull



PD8000 with PHIX330.512.8 ADA Pull



PD5000 with PHIX45714 ADA Pull



PD5000 with PHIX31108 ADA Pull

PD8000 MORTISE LOCK

for Sliding or Pocket Doors



SPECIFICATIONS

Door Thickness	1-3/4" (45mm) Standard Thick Door Kits available
Thin Pocket Door Options	1-3/8" (35mm) use FH17, FH27SL, FH22CF, or FH23CF flush pull options
Handing	Non-Handed
Thumbturn Spindle	5mm x 5mm square
Deadbolt	1" (25.4mm) for 2-3/4" or 2-1/2" backset 3/4" (19mm) for 2" backset
Cylinder	Schlage C keyway 5 pin mortise cylinder with 2 keys (KD). Keying Services available, order separately
Lockcase	Heavy Gauge Steel
Deadbolt and Edge Pull	Brass and Stainless Steel

FEATURES

- Unique improvements not found in standard mortise locks, including patented gravity-powered wing bolts that work much more quietly than standard bolts
- Designer flush pulls and ADA compliant surface pulls in a wide array of beautiful finishes that accent and complement any decor
- Stainless Steel construction for maximum durability and longevity

STANDARD FINISHES

- Surface Pull standard finishes, please see pages 55-57
- Flush Pull standard finishes, please see page 41


For additional finish options not listed, contact Sales Department for MOQ and lead times

PD8000 MORTISE COMPONENTS AND DIMENSIONS

for Sliding or Pocket Doors

PD84: Lockcase with Deadbolt and Edge Pull

Available in 3 backsets: 2", 2-1/2", and 2-3/4"



1. Brass deadbolt with 1" throw for 2-3/4" or 2-1/2" backset and 3/4" throw for 2" backset
2. Self-retracting hook with non-marring latch bolt
3. Spring-loaded edge pull with unique internal sound buffer
4. Solid brass push button
5. Stainless steel faceplate, 2mm thick
6. Vertically adjustable strike (shown)

LOCK OPTIONS



PD80 (2-3/4" Backset)
PD80A (2-1/2" Backset)
PD80B (2" Backset)

- Lockcase with Edge Pull for pocket door
- No Deadbolt
- No Deadbolt or Cylinder



PD81 (2-3/4" Backset)
PD81A (2-1/2" Backset)
PD81B (2" Backset)

- Lockcase with built-in Edge Pull and Dust Proof Strike for inactive pair pocket door



PD82 (2-3/4" Backset)
PD82A (2-1/2" Backset)
PD82B (2" Backset)

- Lockcase with built-in Dust Proof Strike for an inactive pair sliding door
- No Edge Pull



PD83 (2-3/4" Backset)
PD83A (2-1/2" Backset)
PD83B (2" Backset)

- Lockcase with Deadbolt for sliding door
- No Edge Pull
- Less Cylinder




PD84 (2-3/4" Backset)
PD84A (2-1/2" Backset)
PD84B (2" Backset)

- Lockcase with Deadbolt and Edge Pull for pocket door


PD8000 FUNCTIONS

Sliding Door




PD8215
Passage with Lockcase as Dust Proof Strike

- Lockcase used as dust proof strike on pair of doors, inactive side




BTB
Dummy/Passage without Lock Case




PD8340
Privacy with Emergency Release

- Deadbolt operated by inside thumbturn or outside emergency release coin turn



PD8350
Entry with Single Cylinder


- Key outside or thumbturn inside retracts deadbolt



PD8360
Patio


- Deadbolt operated by thumbturn from inside only

Pocket Door




PD8010
Passage with Lockcase

- Used as flush pull or matching trim on pairs of doors
- Edge finger pull operated by push button




PD8115
Passage with Lockcase as Dust Proof Strike

- Lockcase used as dust proof strike on pair of doors, inactive side
- Edge finger pull operated by push button




DP
Dummy/Passage without Lock Case

- No Edge pull




PD8440
Privacy with Emergency Release

- Deadbolt operated by inside thumbturn or outside emergency release coin turn
- Edge finger pull operated by push button



PD8450
Entry with Single Cylinder

- Key outside or thumbturn inside retracts deadbolt
- Edge finger pull operated by push button



PD8460
Patio

- Deadbolt operated by thumbturn from inside only
- Edge finger pull operated by push button

PD5000 MORTISE LOCK

for Sliding or Pocket Doors



SPECIFICATIONS

Door Thickness	1-3/4" (45mm) Standard Thick Door Kits available
Thin Pocket Door Options	1-3/8" (35mm) use FH17, FH27SL, FH22CF, or FH23CF flush pull options
Handing	Non-Handed
Thumbturn Spindle	5mm x 5mm square
Deadbolt	1" (25.4mm) for 2-3/4" or 2-1/2" backset 3/4" (19mm) for 2" backset
Cylinder	Schlage C keyway 5 pin mortise cylinder with 2 keys (KD) Keying Services available; order separately
Lockcase	Heavy Gauge Steel
Deadbolt & Edge Pull	Brass and Stainless Steel
Faceplate & Strike	Stainless Steel

FEATURES


- Provides new possibilities for sliding door locks, with a variety of residential and commercial applications
- Constructed of heavy gauge steel and coupled with beautiful designer flush and surface pull options
- Array of beautiful, long-lasting finishes including ceramic coating options for aesthetic perfection

STANDARD FINISHES

- Surface Pull standard finishes, please see pages 55-57
- Flush Pull standard finishes, please see page 42

For additional finish options not listed, contact Sales Department for MOQ and lead times

PD5000 COMPONENTS AND DIMENSIONS



LOCK OPTIONS



PD50 (2-1/2" / 2-3/4" Backset)
PD50B (2" Backset)

- Lock Case with Edge Pull

PD52 (2-1/2" / 2-3/4" Backset)
PD52B (2" Backset)


- Lockcase with built-in Dust Proof Strike for inactive pair of sliding doors
- No Edge Pull

PD53 (2-3/4" Backset)
PD53A (2-1/2" Backset)
PD53B (2" Backset)

- Lockcase with Deadbolt
- No Edge Pull

PD5000 FUNCTIONS


Sliding Door



PD5215


Passage with Lockcase as Dust Proof Strike

- Lockcase used as dust proof strike on pair of sliding doors, inactive side



BTB


Dummy/Passage without Lock Case



PD5340

Privacy with Emergency Release


- Deadbolt operated by inside thumbturn or outside emergency release coin turn



PD5350

Entry with Single Cylinder

- Key outside or Thumbturn inside retracts deadbolt




PD5360

Patio

- Deadbolt operated by Thumbturn from inside only


Pocket Door



PD5010

Passage with Lockcase

- Used as flush pull or matching trim on pairs of pocket doors
- Edge finger pull operated by push button











DP


Dummy/Passage without Lock Case

- No Edge pull


PD5000 & PD8000 THUMBTURN ROUND OPTIONS




PD5000 & PD8000 THUMBTURN SQUARE OPTIONS




GS07




GS04




GS02




SR07




SR04




SR02



GS Coin Turn Release



GS Coin Turn Release and Indicator



SR Coin Turn Release

PD8000, PD5000 MORTISE LOCKS & PD2000 TWISTLOCK with Flush Pulls for Pocket Doors



PD8000 with FH27 Linear Flush Pull



PD8000 with FH31 Regal Flush Pull



PD5000 with FH22 Luna Flush Pull



PD2000 TwistLock™ Edge-Pull Privacy Lock

FH17 BEZEL FLUSH PULL


PD8000/PD5000 for Sliding or Pocket Doors



SPECIFICATIONS

Standard Door Thickness	1-3/8" to 1-3/4" (35mm to 45mm) Thick Door Kits available
Backset	2-3/4" (70mm), 2-1/2" (63.5mm) and 2" (50.8mm)
Handing	Non-Handed
Thumbturn Spindle	5x5mm square
Deadbolt	1" (25.4mm) for 2-3/4" or 2-1/2" backset 3/4" (19mm) for 2" backset
Cylinder	Schlage C keyway 5 pin mortise cylinder with 2 keys (KD). Keying services available; order separately
Material	Stainless Steel/Brass

DIMENSIONS



TRIM OPTIONS



FH1700
Flush Pull Only



FH1792
Flush Pull with TT09
Thumbturn



FH1704
Flush Pull with
Thumbturn Release



FH1703
Flush Pull with
Cylinder Hole

FH27 / FH27SL LINEAR FLUSH PULL


PD8000/PD5000 for Sliding or Pocket Doors



SPECIFICATIONS

Standard Door Thickness	1-3/4" (45mm) Thick Door Kits available
Backset	2-3/4" (70mm), 2-1/2" (63.5mm) and 2" (50.8mm)
Slim Trim	Slim Trim (FH27SL) available for 1-3/8" (35mm) doors
Handing	Non-Handed
Thumbturn Spindle	5x5mm square
Deadbolt	1" (25.4mm) for 2-3/4" or 2-1/2" backset 3/4" (19mm) for 2" backset
Cylinder	Schlage C keyway 5 pin mortise cylinder with 2 keys (KD). Keying services available; order separately
Material	Stainless Steel/Brass

DIMENSIONS



TRIM OPTIONS



FH2700 FH2700SL
Flush Pull Only



FH2792 FH2792SL
Flush Pull with TT09
Thumbturn



FH2704 FH2704SL
Flush Pull with
Thumbturn Release



FH2703*
Flush Pull with
Cylinder Hole



FH2782*
Flush Pull with
TT08 Thumbturn

* Not available with SL

FH29 ARC FLUSH PULL


PD8000/PD5000 for Sliding or Pocket Doors



SPECIFICATIONS

Standard Door Thickness	1-3/4" (45mm) Thick Door Kits available
Backset	2-3/4" (70mm), 2-1/2" (63.5mm) and 2" (50.8mm)
Handing	Non-Handed
Thumbturn Spindle	5x5mm square
Deadbolt	1" (25.4mm) for 2-3/4" or 2-1/2" backset 3/4" (19mm) for 2" backset
Cylinder	Schlage C keyway 5 pin mortise cylinder with 2 keys (KD). Keying services available; order separately
Material	Stainless Steel/Brass

DIMENSIONS



TRIM OPTIONS



FH2900
Flush Pull Only



FH2992
Flush Pull with TT09
Thumbturn



FH2904
Flush Pull with
Thumbturn Release



FH2903
Flush Pull with
Cylinder Hole



FH2982
Flush Pull with
TT08 Thumbturn

FH31 REGAL FLUSH PULL


PD8000/PD5000 for Sliding or Pocket Doors



SPECIFICATIONS

Standard Door Thickness	1-3/4" (45mm) Thick Door Kits available
Backset	2-3/4" (70mm), 2-1/2" (63.5mm) and 2" (50.8mm)
Handing	Non-Handed
Thumbturn Spindle	5x5mm square
Deadbolt	1" (25.4mm) for 2-3/4" or 2-1/2" backset 3/4" (19mm) for 2" backset
Cylinder	Schlage C keyway 5 pin mortise cylinder with 2 keys (KD). Keying services available; order separately
Material	Stainless Steel/Brass

DIMENSIONS



TRIM OPTIONS



FH3100
Flush Pull Only



FH3103
Flush Pull
with Cylinder Hole



FH3182
Flush Pull with
TT08 Thumbturn



FH3192
Flush Pull with
TT09 Thumbturn



FH3104
Flush Pull with
Thumbturn Release

FH32 CROWN FLUSH PULL


PD8000/PD5000 for Sliding or Pocket Doors



SPECIFICATIONS

Standard Door Thickness	1-3/4" (45mm) Thick Door Kits available
Backset	2-3/4" (70mm), 2-1/2" (63.5mm) and 2" (50.8mm)
Handing	Non-Handed
Thumbturn Spindle	5x5mm square
Deadbolt	1" (25.4mm) for 2-3/4" or 2-1/2" backset 3/4" (19mm) for 2" backset
Cylinder	Schlage C keyway 5 pin mortise cylinder with 2 keys (KD). Keying services available; order separately
Material	Stainless Steel/Brass

DIMENSIONS



TRIM OPTIONS



FH3200
Flush Pull Only



FH3203
Flush Pull
with Cylinder Hole



FH3282
Flush Pull with
TT08 Thumbturn



FH3292
Flush Pull with
TT09 Thumbturn



FH3204
Flush Pull with
Thumbturn Release

FH22 LUNA FLUSH PULL


PD8000/PD5000 for Sliding or Pocket Doors



SPECIFICATIONS

Standard Door Thickness	1-3/4" (45mm) Thick Door Kits available
Backset	2-3/4" (70mm), 2-1/2" (63.5mm) and 2" (50.8mm)
Handing	Non-Handed
Thumbturn Spindle	5x5mm square
Deadbolt	1" (25.4mm) for 2-3/4" or 2-1/2" backset 3/4" (19mm) for 2" backset
Cylinder	Schlage C keyway 5 pin mortise cylinder with 2 keys (KD). Keying services available; order separately
Material	Stainless Steel/Brass

DIMENSIONS



TRIM OPTIONS




FH2200
Flush Pull Only



FH2204
Flush Pull with
Thumbturn Release



FH2203*
Flush Pull with
Cylinder Hole



FH2282*
Flush Pull with
TT08 Thumbturn

* Not available with CF

FH22CF LUNA CONCEALED FIXING FLUSH PULL


PD8000/PD5000 for 1-3/8" or thicker Sliding or Pocket Doors



SPECIFICATIONS

Standard Door Thickness	1-3/8" (35mm) & 1-3/4" (45mm) Thick Door Kits available
Backset	2-3/4" (70mm), 2-1/2" (63.5mm) and 2" (50.8mm)
Handing	Non-Handed
Thumbturn Spindle	5x5mm square
Deadbolt	1" (25.4mm) for 2-3/4" or 2-1/2" backset 3/4" (19mm) for 2" backset
Material	Stainless Steel

DIMENSIONS



TRIM OPTIONS



FH2200CF
Flush Pull Only



FH2204CF
Flush Pull with
Thumbturn Release



FH2262CF
Flush Pull with
TT06 Thumbturn

FH23 URBAN FLUSH PULL


PD8000/PD5000 for Sliding or Pocket Doors



SPECIFICATIONS

Standard Door Thickness	1-3/4" (45mm) Thick Door Kits available
Backset	2-3/4" (70mm), 2-1/2" (63.5mm) and 2" (50.8mm)
Handing	Non-Handed
Thumbturn Spindle	5x5mm square
Deadbolt	1" (25.4mm) for 2-3/4" or 2-1/2" backset 3/4" (19mm) for 2" backset
Cylinder	Schlage C keyway 5 pin mortise cylinder with 2 keys (KD). Keying services available; order separately
Material	Stainless Steel/Brass

DIMENSIONS



TRIM OPTIONS




FH2300
Flush Pull Only



FH2304
Flush Pull with
Thumbturn Release



FH2303*
Flush Pull with
Cylinder Hole



FH2382*
Flush Pull with
TT08 Thumbturn

* Not available with CF

FH23CF URBAN CONCEALED FIXING FLUSH PULLS


PD8000/PD5000 for 1-3/8" or thicker Sliding or Pocket Doors



SPECIFICATIONS

Standard Door Thickness	1-3/8" (35mm) & 1-3/4" (45mm) Thick Door Kits available
Backset	2-3/4" (70mm), 2-1/2" (63.5mm) and 2" (50.8mm)
Handing	Non-Handed
Thumbturn Spindle	5x5mm square
Deadbolt	1" (25.4mm) for 2-3/4" or 2-1/2" backset 3/4" (19mm) for 2" backset
Material	Stainless Steel

DIMENSIONS



TRIM OPTIONS



FH2300
Flush Pull Only



FH2362CF
Flush Pull with
Thumbturn



FH2304CF
Flush Pull with
Thumbturn Release

PD2000 TWISTLOCK EDGE PULL PRIVACY LOCK

Locking Edge Pull for Pocket Doors



SPECIFICATIONS

Door Thickness	Standard Trim: 1-3/8" (35mm) to 1-3/4" (45mm)
	Concealed Fastener Trim: 1-3/4" (45mm) Thick door kit available, please contact the sales department
Backset	2-3/8" (60mm)
Bolt Projection	5/8" (15.5mm)
Thumbturn Spindle	5 x 5mm square
Handing	Non-Handed

STANDARD FINISHES

- 32D Satin Stainless Steel
- 19G Graphite Black
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze


For additional finish options not listed, contact Sales Department for MOQ and lead times

FEATURES

- Privacy pocket door lock with edge pull combination
- Utilizes a unique rotating bolt to lock into the strike
- Edge pull operates a 2-in-1 spring-loaded pull and locking bolt
- Designed to fit in standard 2-1/8" bore
- Commercially tested with 200,000 cycle test
- User-friendly emergency coin release from the outside


FUNCTION

Privacy Lock with Edge Pull: PD2062



- Spring-loaded edge pull activated by pressing on front end. Once edge pull is inserted into strike, rotate thumbturn on recessed trim to rotate pull inside strike, transforming it into a deadbolt.
- Unlock by turning thumbturn back, or via emergency coin release on outside of door. Push deadbolt/edge pull back into lockcase when not in use.

Passage/Edge Pull: PD2061





- Spring-loaded edge pull is activated by pressing on front end.
- Recessed flush trim assists closing and opening of door.

PD2000 TWISTLOCK EDGE PULL PRIVACY LOCK


Locking Edge Pull for Pocket Doors

PD2000 COMPONENTS




PD2000 Lock

Lock case only:
PD2060 2-3/8" Backset




STANDARD TRIM



Item Codes	Trim	Thumbturn	Backset	Lock/Function
FH12 PD2061	FH12	TT08	2-3/8"	Passage
FH12 PD2062	FH12	TT08	2-3/8"	Privacy
FH13 PD2061	FH13	TT08	2-3/8"	Passage
FH13 PD2062	FH13	TT08	2-3/8"	Privacy

OPTIONAL TRIM



Item Codes	Trim*	Thumbturn	Backset	Lock/Function
FH22CF PD2061	FH22CF	TT06	2-3/8"	Passage
FH22CF PD2062	FH22CF	TT06	2-3/8"	Privacy
FH23CF PD2061	FH23CF	TT06	2-3/8"	Passage
FH23CF PD2062	FH23CF	TT06	2-3/8"	Privacy

*FH22CF/FH23CF compatible with 1-3/4" Thick Door Only

PD8000/PD5000 FACEPLATE AND STRIKE



- PD-84-FP** (Standard 1" Faceplate)
PD-84-FP114 (Optional 1-1/4" Faceplate)
 • Lockcase with Deadbolt and Edge Pull: Entry, Privacy, Patio



- PD-80-FP** (Standard 1" Faceplate)
PD-80-FP114 (Optional 1-1/4" Faceplate)
 • Lockcase with Edge Pull, No Deadbolt: Passage



- PD-83-FP** (Standard 1" Faceplate)
PD-83-FP114 (Optional 1-1/4" Faceplate)
 • Lockcase with Deadbolt, No Edge Pull: Entry, Privacy, Patio



- PD-81-FP** (Standard 1" Faceplate)
PD-81-FP114 (Optional 1-1/4" Faceplate)
 • Lockcase with Build-in Edge Pull: Passage Inactive



- PD-82-FP** (Standard 1" Faceplate)
PD-82-FP114 (Optional 1-1/4" Faceplate)
 • Lockcase with Built-in Dust Proof Strike: Passage Inactive



- PD-53-FP** (Standard 1" Faceplate)
PD-53-FP114 (Optional 1-1/4" Faceplate)
 • Lockcase with Deadbolt: Entry, Privacy, Patio



- PD-50-FP** (Standard 1" Faceplate)
PD-50-FP114 (Optional 1-1/4" Faceplate)
 • Lockcase with Edge Pull: Passage



- PD-52-FP** (Standard 1" Faceplate)
PD-52-FP114 (Optional 1-1/4" Faceplate)
 • Lockcase with Built-in Dust Proof Strike: Passage Inactive

HOW TO ORDER

PD8000 Mortise Locks for Sliding Doors

To order, please describe the additional requirements in the same sequence as below. Please see Price Book for additional parts or service upcharges.

Function	Backset	Cylinder	Thumbturn	Indicator	Finish
PD8350	A	-S6	-GR02		-32D
1	2	3	4	5	6

FUNCTION

8010 Passage

8215 Passage with dust-proof strike

8340 Privacy

8350 Entry

8360 Patio

PD8215 passage function is not compatible with thumbturn and cylinder

To order PD8000 Mortise Locks with Surface Pulls for sliding doors, order lockcase [backset / cylinder / thumbturn].

Surface Pull will need to be ordered as a separate line item, either bolt-thru single pull or back-to-back double pulls.

Example: **PHIX30108-BTB-32D**

PD8350A-S6-GR04-32D

2 BACKSET

Backset Blank = 2-3/4"

Backset A = 2-1/2"

Backset B = 2"

3 CYLINDER AND HOUSING (includes collar)

LC = Less Cylinder



Blank = Standard Mortise 1-1/4" Cylinder



-S6 = Small Format Interchangeable Cylinder (SFIC) Housing 1-1/4", 6-Pin, Less Core, L Clover Cam

-S7 = Small Format Interchangeable Cylinder (SFIC) Housing 1-3/8", 7-Pin, Less Core, L Clover Cam

-L6 = Large Format Interchangeable Cylinder (LFIC) Housing 1-1/2", 6-Pin, Less Core, L Clover Cam



Order IC Cores and Thick Door Kits (TDKs) separately

4 THUMBTURN



GR02

GT02

GS02

SR02



GR04

GT04

GS04

SR04



Blank = GR07

GT07

GS07

SR07

See page 24 and 25 for detailed thumbturn option designs

5 INDICATOR

Blank = Without Indicator

-W = With Indicator

Only GT and GS rosettes are compatible with thumbturn indicator

6 FINISH

Standard:



-32D



-C19G



-C19



-CGY



-CBD



-32



-PVD4



19G

PVD4 finish available for PHIX330.512.8 Surface Pull

Special Order Finishes subject to minimum order quantity, extended lead-time and upcharge. Contact Sales Department for details.

HOW TO ORDER

PD5000 Mortise Locks for Sliding Doors

To order, please describe the additional requirements in the same sequence as below. Please see price book for parts or additional service upcharge.

Function	Backset	Cylinder	Thumbturn	Indicator	Finish
PD5340	A	-S6	-GT04		-32D
1	2	3	4	5	6

FUNCTION

5010 Passage
5215 Passage with Dust-proof Strike
5340 Privacy
5350 Entry
5360 Patio

To order the PD5000 Mortise Locks with Surface Pulls for sliding doors, order lockcase [backset /cylinder / thumbturn].
Surface Pull will need to be ordered as a separate line item, either bolt-thru single pull or back-to-back double pulls.
Example: **PD5340A-S6-GT04-32D**
PHIX330.512.8-BTB-32D

2 BACKSET

Backset Blank = 2-3/4"

Backset A = 2-1/2"

Backset B = 2"

3 CYLINDER AND HOUSING

LC = Less Cylinder



Blank = Standard Mortise 1-1/4" Cylinder



-S6 = Small Format Interchangeable Cylinder (SFIC) Housing 1-1/4", 6-Pin, Less Core, L Clover Cam
-S7 = Small Format Interchangeable Cylinder (SFIC) Housing 1-3/8", 7-Pin, Less Core, L Clover Cam
-L6 = Large Format Interchangeable Cylinder (LFIC) Housing 1-1/2", 6-Pin, Less Core, L Clover Cam



Order IC Cores and Thick Door Kits (TDKs) separately

4 THUMBTURN



GR02
GT02
GS02
SR02



GR04
GT04
GS04
SR04



Blank = GR07
GT07
GS07
SR07

See page 24 and 25 for detailed thumbturn option designs

5 INDICATOR

Blank = Without Indicator
-W = With Indicator

Only GT and GS rosettes are compatible with thumbturn indicator

6 FINISH

Standard:



-32D



-C19G



-C19



-CGY



-CDB



-32



-PVD4



19G

PVD4 finish available for PHIX330.512.8 Surface Pull

Special Order Finishes subject to minimum order quantity, extended lead-time and upcharge.
Contact Sales Department for details.

HOW TO ORDER

PD8000 Mortise Locks with Flush Pulls for Pocket Doors

To order, please describe the additional requirements in the same sequence as below. Please see Price Book for additional parts or service upcharges.

Flush Pull	Function	Backset	Thumbturn	Finish
FH27	PD8450	A		-32D
1	2	3	4	5
FLUSH PULL			FUNCTION	
     			8010 Passage 8115 Passage with dust-proof strike 8440 Privacy 8450 Entry 8460 Patio	
   				
FH17 FH27 FH27SL FH29 FH31 FH32				
FH22 FH23 FH22CF FH23CF				

NOTE: PD8115 and PD8450 Locks are not suitable for FH22CF and FH23CF Trim, PD8450 is not suitable for FH27SL

3 BACKSET

Backset Blank = 2-3/4"

Backset A = 2-1/2"

Backset B = 2"

4 THUMBTURN

Blank = Privacy with TT08

(FH22 and FH23 are only available with TT08,
FH22CF and FH23CF feature a unique TT06 turn
and are not available with TT08 or TT09)

TT09= Privacy with TT09

(FH17, FH27SL are only available with TT09)

5 FINISH

	FH17	FH27	FH27SL	FH29	FH31	FH32	FH22	FH23	FH22CF	FH23CF
Standard -32D	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
-32	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
-10B	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
-4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
-19G	✓	✓	✓						✓	✓
-15		✓	✓	✓	✓	✓	✓		✓	
-26D		✓	✓	✓	✓	✓	✓	✓	✓	✓
-26		✓	✓				✓			
-38		✓	✓	✓	✓	✓	✓	✓	✓	✓
-14		✓	✓	✓	✓	✓	✓			
-3							✓	✓		

Special Order Finishes subject to minimum order quantity, extended lead-time and upcharge.
Contact Sales Department for details.

HOW TO ORDER

PD5000 Mortise Locks with Flush Pulls for Pocket Doors

To order, please describe the additional requirements in the same sequence as below. Please see price book for parts or additional service upcharge.

Flush Pull	Function	Backset	Thumbturn	Finish
FH27 1	PD5440 2	B 3	4	-32D 5
FLUSH PULL		FUNCTION		
 FH17  FH27  FH27SL  FH29  FH31  FH32		5010 Passage 5215 Passage with Dust-proof Strike 5340 Privacy 5350 Entry 5360 Patio		
 FH22  FH23  FH22CF  FH23CF				

NOTE: PD5010 Lock is not suitable for FH22CF and FH23CF Trim, PD5350 is not suitable for FH27SL Trim

3 BACKSET

Backset Blank = 2-3/4"

Backset A = 2-1/2"

Backset B = 2"

4 THUMBTURN

Blank = Privacy with TT08

(FH22 and FH23 are only available with TT08,
FH22CF and FH23CF feature a unique TT06 turn
and are not available with TT08 or TT09)

TT09= Privacy with TT09

(FH17,FH27SL are only available with TT09)

5 FINISH


	FH17	FH27	FH27SL	FH29	FH31	FH32	FH22	FH23	FH22CF	FH23CF
Standard -32D	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
-32	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
-10B	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
-4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
-19G	✓	✓	✓						✓	✓
-15		✓	✓	✓	✓	✓	✓		✓	
-26D		✓	✓	✓	✓	✓	✓	✓	✓	✓
-26		✓	✓				✓			
-38		✓	✓	✓	✓	✓	✓	✓	✓	✓
-14		✓	✓	✓	✓	✓	✓			
-3							✓	✓		

Special Order Finishes subject to minimum order quantity, extended lead-time and upcharge.
Contact Sales Department for details.

HOW TO ORDER

PD2000 TwistLock Edge Pull Privacy Lock

To order, please describe the additional requirements in the same sequence as below. Please see price book for parts or additional service upcharge.



3 FINISH

			FH12	FH13	FH22CF	FH23CF
Standard	-32D		√	√	√	√
	-32		√	√	√	√
	-4		√	√	√	√
	-19G		√	√	√	√


Special Order Finishes subject to minimum order quantity, extended lead-time and upcharge. Contact Sales Department for details.

BD4000 & BD1000 BARN DOOR LOCKS

for Residential, Hospitality and Multi-Family Applications



BD4000



BD4000



BD1000

BD4000 CONCEALED JAMB MOUNT

Barn Door Privacy Lock




SPECIFICATIONS

Material	Trim: Stainless Steel Lockcase: Steel Lockbolt: Stainless Steel Strike: Stainless Steel
Lock Bolt	1/2" (13mm) Diameter
Drive-in Bolt Casing	1" (25mm) Diameter Strike mounted in Barn Door for standard door thickness: 1-3/8" (35mm) to 1-3/4" (45mm) Thick Door Kits Available
Backset	2-1/4" (57mm) and 3-1/2" (89mm)
Handing	Non-handed
Hub and Spindle	5mm x 5mm square

FEATURES

- Innovative engineering places lock inside jamb and dust-proof strike inside door (reverse of typical door locks)
- No need to build out extra frames
- Can retrofit into existing jambs and doors
- Discrete release key provided for emergency opening
- Eight trim options, including ADA compliant thumbturn
- Surpassed ANSI 156.36 grade 3 cycle testing



STANDARD FINISHES


- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- 10B Oil Rubbed Bronze
- 4 Satin Brass
- 19G Graphite Black
- 26D Satin Chrome
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze

For additional finish options not listed, contact Sales Department for MOQ and lead times

BD4000 CONCEALED JAMB MOUNT

Barn Door Privacy Lock

WALL THICKNESS



APPLICATION



- A simple and elegant privacy lock for barn door openings for either residential or commercial applications, without having to build out extra frames
- Tubular drive-in bolt installed inside the jamb
- Dust-proof strike installed in the door
- Discreet release button with decorative cap installed on outside of the door for emergency release
- A variety of trim escutcheon and thumbturn options installed on jamb side to allow locking and unlocking of bolt from inside
- ADA thumbturn available, perfect for commercial and hospitality applications

OVERLAP

Door Overlap is the distance from the edge of the door to the edge of the wall. Measure the Door Overlap on the lock side when the door is fully closed.

NOTE: Standard door opening walls have 2 wood studs behind drywall or trim casing

WALL THICKNESS



BD4000 FLUSH TRIM

Barn Door Privacy Lock



FEATURES

- Designed for maximum aesthetics without visible screws or fasteners
- Two beautiful contemporary designs
- Smooth stainless steel thumbturn sits flush against the jamb when not in use
- Not ADA compliant

OPTIONAL FACE PLATE


Protects wall from possible damage
INOX Laser Art designs available
Order **BD-FPC**



THICK DOOR KIT FOR DOORS 2" AND UP

Available for doors up to 3" thick
Includes extended screw and extended release
For thicker doors, please contact an INOX sales representative

Door Thickness:
2" (51.8mm) ~ 3" (76.2mm)



SPACER RING

Lock bolt has 1" projection, allows up to 1/2" door to wall gap. Extra spacer ring accommodates up to 3/4" gap between barn door and wall.

STANDARD FINISHES

- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- 10B Oil Rubbed Bronze
- 4 Satin Brass
- 19G Graphite Black
- 26D Satin Chrome
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze

For additional finish options not listed, contact Sales Department for MOQ and lead times

BD4000 CONCEALED JAMB MOUNT FOR METAL STUDS

Barn Door Privacy Lock




FEATURES

- Engineered for walls with metal studs oriented opposite of each other
- Reinforcement bracket strengthens lockbolt
- Unique design allows flexible lock placement in wall


INSTALLATION OPTIONS

A:




A. (above) requires a 2-1/8" bore through first stud to allow installation on second stud. For B. and C. (below), install bracket on first stud.


B:



C:




D:




D. (above) requires a special bracket that is only compatible with the rectangular trim shown. This prep requires a 2-1/4" bore on the first stud to allow bracket installation.

ORIENTATION OF METAL STUDS


- A. Overlapping - flat surface toward jamb
- B. Overlapping - flat surface away from jamb
- C. Studs back to back
- D. Studs form box (special bracket needed)



Standard bracket for installations A, B, and C, shown with EC1217 Rose and Thumbturn




Special bracket, faceplate, and exploded diagram of lock for installation D, shown with TT17 Thumbturn




BD4000 PRIVACY LOCK TRIM OPTIONS


ESCUTCHEONS & THUMBTURNS




EC1216




EC1314




EC1515




FH2262CF*




EC1217



EC1315




EC1517




FH2362CF*


ESCUTCHEONS & THUMBTURNS FOR METAL STUD




EC3216




EC3314




EC3515



EC3217



EC3315



EC3517

* CF stands for Concealed Fixing

HOW TO ORDER

PD4000 Privacy Lock for Barn Door

To order, please describe the additional requirements in the same sequence as below. Please see price book for parts or additional service upcharge.

Rose/Thumbturn	Backset	Option	Finish
EC1315 ①	BD4214 ②	MS ③	-32D ④
ROSE/THUMBTURN			
			
			
			
			
			
			

* for Metal Stud

2 BACKSET

BD4214 = 2-1/4"

BD4312 = 3-1/2"

3 OPTION

MS Metal Stud

NOTE: Metal Stud (MS) only applies to structure D

4 FINISH

		EC1216	EC1217	EC1314	EC1315	EC1515	EC1517	FH22CF	FH23CF
Standard	-32D		✓	✓	✓	✓	✓	✓	✓
	-32		✓	✓	✓	✓	✓	✓	✓
	-10B		✓	✓	✓	✓	✓	✓	✓
	-4		✓	✓	✓	✓	✓	✓	✓
	-19G		✓	✓	✓	✓	✓	✓	✓
	-26D		✓	✓	✓	✓	✓	✓	✓

Special Order Finishes subject to minimum order quantity, extended lead-time and upcharge.
Contact Sales Department for details.

BD1000 SURFACE MOUNT

Barn Door Privacy Lock



SPECIFICATIONS

Material	Stainless Steel
Lockcase	3-9/16" x 1-7/8" x 9/16"
Standard Thumb-lever	13/16" (20mm) (order BD1022)
ADA Thumb-lever	1-9/16" (order BD1023)

FEATURES

- Installs on any type of wall or jamb casing
- Easy, quick installation—field reversible
- No need to drill drywall or studs; protects decorative molding
- Perfect for renovation or remodeling
- Two thumb levers available, including ADA option




BD1022
Standard 13/16"
Thumb lever



BD1023
ADA 1-9/16"
Thumb lever

DIMENSIONS



STANDARD FINISHES

- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- 10B Oil Rubbed Bronze
- 4 Satin Brass
- 19G Graphite Black
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze

For additional finish options not listed, contact Sales Department for MOQ and lead times

WS90 WALL STRIKE

for Lockable Sliding Barn Doors



SPECIFICATIONS

Door Thickness	1-3/4" (45mm) Thick door kits available
Strike Case Size	2-7/16" x 1-3/4" x 1-9/16" (61.5mm x 44.75mm x 40mm)
Strike Opening Size	1-3/8" x 5/8" (35mm x 16mm)
Material	304 Stainless Steel
Handing	Non-Handed

APPLICATION

Surface-mounted strike that enables sliding and barn doors to latch or lock. WS90 is the only modern design surface-mounted Wall Strike that works with sliding and barn doors.


Suitable for use with the INOX PD5000, PD8000, or PD9500. WS90 can be used in a wide range of applications, including but not limited to:

- Hospitality
- Multi-family & Mixed Use
- Commercial & Industrial
- Office Buildings

FEATURES

- Designed as an effective, aesthetic solution to enable sliding and barn doors to surface latch
- Unique installation design ensures maximum strength and security via an interlocking mounting
- Concealed fixing with no visible set screws prevents hardware tampering
- Stainless Steel for maximum durability and high tolerance against heat and fire

DIMENSIONS



STANDARD FINISHES

- 32D Satin Stainless Steel
- 19G Graphite Black
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze

For additional finish options not listed, contact Sales Department for MOQ and lead times

WS90L LARGE WALL STRIKE

for Lockable Sliding Barn Doors



SPECIFICATIONS

Door Thickness	1-3/4" (45mm) Thick door kits available
Strike Case Size	4-1/4" x 1-3/4" x 1-9/16" (108mm x 45mm x 40mm)
Strike Opening Size	1-3/8" x 5/8" (35mm x 16mm)
Material	304 Stainless Steel
Handing	Non-Handed

APPLICATION

WS90L is the only modern design surface-mounted Wall Strike that works with self-latching, self-locking sliding doors. It is suitable for use with the INOX PD96. WS90L can be used in a wide range of applications, including but not limited to: Hospitality, Multi-family & Mixed Use, Commercial & Industrial, Office Buildings


ADDITIONAL SPACERS

Part Number	Description
WS90L-SP2	2mm Spacer
WS90L-SP3	3mm Spacer

FEATURES

- Advanced engineered chassis; easily installed with no special tools
- Designed for use with the INOX PD96 lock
- Vandal-resistant anchored bracket
- Concealed fixing with no visible set screws prevents hardware tampering
- Vertically adjustable up to 1/2" for ease of installation
- Stainless Steel for maximum durability and high tolerance against heat and fire

DIMENSIONS




STANDARD FINISHES

- 32D Satin Stainless Steel
- 19G Graphite Black
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze

For additional finish options not listed, contact Sales Department for MOQ and lead times

AMERICAN WITH DISABILITIES ACT COMPLIANCE




INOX ADA compliant pocket door hardware meets the "no grasp" and "no pinch" requirements of ADA Standard 4.13.9. The pocket door opening must have a clear width of 32" according to ADA Standard 404.2.3*. When sliding doors are fully open, operating hardware shall be exposed and usable from both sides.

To accommodate these requirements, the total pocket door opening must be a MINIMUM of 40". The door must protrude a minimum of 4" from the jamb in order to install the ADA pocket door hardware on the door.

The hardware must be installed 34" above the finished floor or ground, giving the hardware a height of 47" (the maximum is 48") from the finished floor, meeting ADA Standard 404.2.7.

***ADA Standard 404.2.3 is from the Department of Justice ADA Publication dated September 15, 2012. Unison Hardware, Inc. recommends the end user double check all State and Federal standards for your particular project.**


ADA COMPLIANT SURFACE PULL OPTIONS



PHIX31108

STANDARD FINISHES



- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- 19G Graphite Black
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze



PHIX41714

STANDARD FINISHES


- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- 19G Graphite Black
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze



PHIX330.512.8

STANDARD FINISHES


- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- 19G Graphite Black
- 26D Satin Chrome
- PVD4 Satin Brass
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze



PHIX30108

STANDARD FINISHES

- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- 19G Graphite Black
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze




PHIX45714

STANDARD FINISHES

- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- 10B Oil Rubbed Bronze
- 19G Graphite Black
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze

For additional finish options not listed, contact Sales Department for MOQ and lead times

SURFACE PULL OPTIONS



FEATURES

- INOX PHIX Series door pulls are crafted with classic, timeless style. They are ideal for biophilic, ADA, and streamlined interior use
- Pulls are designed with clearance that meets ADA compliance specifications when installed in accordance with other ADA requirements (pull height, door opening space, etc.)
- Fixing packs for Bolt-Thru or Back-to-Back installation are included with each order; clear nylon washer and rubber inserts are included for glass door applications upon request

CODE COMPLIANCE



- ANSI A156.6 – J401, J402, J406
- ANSI A117.1 – ADA for barrier free accessibility
- C-UBC - California Amended Uniform Builders Code
- NFPA 80 - National Fire Protection Association
- NFPA 101 - National Fire Protection - Life Safety

STANDARD FINISHES

- 32D Satin Stainless Steel
- 32 Bright Stainless Steel
- 19G Graphite Black (Limited Styles available)
- CeraMax Ceramic Coating: C19G Graphite Black, C19 Flat Black, CGY Stormy Grey, CDB Dark Bronze


For additional finish options not listed, contact Sales Department for MOQ and lead times

Type	Length	CTC	Tube Dia.	Part Number
U Style	6-3/4"	6"	3/4"	PHIX31106
	8-3/4"	8"	3/4"	PHIX31108
	10-3/4"	10"	3/4"	PHIX31110
	12-3/4"	12"	3/4"	PHIX31112
	16-3/4"	16"	3/4"	PHIX311.16.1675
	18-3/4"	18"	3/4"	PHIX311.18.1875
	11"	10"	1"	PHIX31210
	13"	12"	1"	PHIX31212
	13-1/4"	12"	1-1/4"	PHIX31312
	19-1/4"	18"	1-1/4"	PHIX31318


SURFACE PULL OPTIONS

Type	Length	CTC	Tube Dia.	Part Number
T1 Style	12"	9-1/2"	3/4"	PHIX330.912.12
	16"	13-1/2"	3/4"	PHIX330.1312.16
	18"	15-1/2"	3/4"	PHIX330.1512.18
	16"	13-1/4"	1-1/4"	PHIX333.1325.16
	18"	15-1/4"	1-1/4"	PHIX333.1525.18
	36"	33-1/4"	1-1/4"	PHIX333.3325.36
	48"	45-1/4"	1-1/4"	PHIX333.4525.48
T2 Style 90°	16"	12"	1"	PHIX33212
	16"	10"	1"	PHIX332.10.16
	18"	10"	1-1/4"	PHIX33310
	20"	12"	1-1/4"	PHIX33312
	26"	18"	1-1/4"	PHIX33318
	56"	48"	1-1/4"	PHIX33348
	68"	60"	1-1/4"	PHIX33360
T2 Style 45°	72"	64"	1-1/4"	PHIX33364
	18"	10"	1-1/4"	PHIX34310
	20"	12"	1-1/4"	PHIX34312
	26"	18"	1-1/4"	PHIX34318
D Style	11"	10"	1"	PHIX32210
	13"	12"	1"	PHIX32212
	13-1/4"	12"	1-1/4"	PHIX32312
	19-1/4"	18"	1-1/4"	PHIX32318
L Style	8-3/4"	8"	3/4"	PHIX30108
	16-3/4"	16"	3/4"	PHIX301.16.1675
	18-1/4"	18"	1-1/4"	PHIX303.18.1925
L2 Style	12-3/4"	12"	1"	PHIX45012

For additional finish options not listed, contact Sales Department for MOQ and lead times




All Surface Pulls are available as either **Bolt-Thru**, a single pull (function code **BT**) with BT fixing pack; or **Back-to-Back** (function code **BTB**), two pulls and one Back-to-Back fixing pack.



MORTISE CYLINDERS

MORTISE CYLINDERS AND KEYS



Schlage C Keyway, 6 Pin, with Clover Cam, 2 Keys
Standard Keyed Different (KD)
Other Keying Services available
Other sizes or keyway cylinders available. Order separately.

Illustration	Item Code	Description	Size	ANSI
	<i>Mortise Cylinders</i>			
	CMB105	Mortise Cylinder, Schlage C Keyway, 5 pin, L Cam	1"	E09211
	CMB1186	Mortise Cylinder, Schlage C Keyway, 6 pin, L Cam	1-1/8"	E09211
	CMB1146	Mortise Cylinder, Schlage C Keyway, 6 pin, L Cam	1-1/4"	E09211
	CMB1386	Mortise Cylinder, Schlage C Keyway, 6 pin, L Cam	1-3/8"	E09211
	CMB1126	Mortise Cylinder, Schlage C Keyway, 6 pin, L Cam	1-1/2"	E09211
	CMB1346	Mortise Cylinder, Schlage C Keyway, 6 pin, L Cam	1-3/4"	E09211
	<i>Dummy Cylinders</i>			
	CMB1140DM*	Mortise Dummy Cylinders, No Cam	1-1/4"	E09211

* Dummy function lockset does not include dummy cylinder. Dummy cylinder ordered separately if required.

INTERCHANGEABLE (IC) CORE HOUSING WITH REMOVABLE MORTISE CAM

Solid Brass/ Small Format (SFIC) Housing

Standard L Cam included for MC7000 Series mortise lock

Accepts Best, Arrow and Falcon Cores

Illustration	Item Code	Description	Size	ANSI
	CMB1146-ICBA-HUS	SFIC Mortise Cylinder Housing, 6 Pin	1-1/4"	E09241
	CMB1386-ICBA-HUS	SFIC Mortise Cylinder Housing, 6 Pin	1-3/8"	E09241
	CMB1126-ICBA-HUS	SFIC Mortise Cylinder Housing, 6 Pin	1-1/2"	E09241
	CMB1586-ICBA-HUS	SFIC Mortise Cylinder Housing, 6 Pin	1-5/8"	E09241
	CMB1387-ICBA-HUS	SFIC Mortise Cylinder Housing, 7 Pin	1-3/8"	E09241
	CMB1127-ICBA-HUS	SFIC Mortise Cylinder Housing, 7 Pin	1-1/2"	E09241
	CMB1587-ICBA-HUS	SFIC Mortise Cylinder Housing, 7 Pin	1-5/8"	E09241
	CMB1126-LFIC-HUS	LFIC Mortise Cylinder Housing, 6 Pin	1-1/2"	E09241

INTERCHANGEABLE CORES ONLY

Solid brass plug and housing / Small Format (SFIC) Core in Best A Keyway

2 Change keys per Combined Core – A2 System Only

1 master key or grandmaster key included per group/order


1 Control key per group/order

6 or 7 pin cores replace Arrow, Best, Falcon

Construction or Combined Core

Illustration	Item Code	Description	ANSI
	CMB-ICBA6-CST	SFIC Core Only, Best A Keyway, 6 Pin, Construction	E09251
	CMB-ICBA6-CMB	SFIC Core Only, Best A Keyway, 6 Pin, Combined	E09251
	CMB-ICBA7-CMB	SFIC Core Only, Best A Keyway, 7 Pin, Combined	E09251
	CMB-LFIC-SC6-CMB	LFIC Core Only, Schlage C Keyway, 6 Pin, Combined	E09251


KEYS

Illustration	Item Code	Description
	LSK-6SC-NP	Standard key Schlage C Keyway for 6 Pin, Nickel Plated
	LSK01-6SC-NS-DND	DND Nickel Silver Key, Schlage C Keyway for 6 Pin w/ "Do Not Duplicate"
	LSK06-BA-CRK	Extra Control Key for IC Core, Best A Keyway
	LSK06-BA-MK	Extra Master Key for IC Core, Best A Keyway
	LSK06-BA-GMK	Extra Grand Master Key for IC Core, Best A Keyway

KEYING SERVICES

Description	Item No.
Service: Key Cut including Key Blank	SV-KYCT
Service: Keyed Alike (KA)	SV-KA
Service: Keyed Alike Pair	SV-KA2
Service: Keyed Alike Group (Specify Number of Keyed Alike Per Group)	SV-KA (Number)
Service: Keyed to Specific Code	SV-KS
Service: Master Keying	SV-MK
Service: Grandmaster Keying with 2 or more Master groups	SV-GMK
Service: Construction Master Keying Service	SV-CMK
Service: Great Grandmaster Key	SV-GGMK

Description	Item No.
Service: IC Core Key Cut including Key Blank	SV-ICKYCT
Service: IC Core Keyed Alike (KA) - Each cylinder in the group is keyed alike	SV-ICKA
Service: IC Core Keyed to Specific Code - Cylinder is keyed to a specific code	SV-ICKS
Service: IC Core Master Keying - 2 Change Keys per Cylinder and 3 Master Keys per MK	SV-ICMK
Service: IC Core Grand Master Keying (2 or more MK groups included)	SV-ICGMK



Please visit our website
www.inoxproducts.com
for more technical and new product information.

Unison Hardware, Inc.
6 Wayne Court, Sacramento CA 95829, USA Tel: +1.916.388.1888
Email: info@unisonhardware.com