BP / MU UNIVERSAL MULTIPOINT TRIM



Parts and Services

Euro Cylinders

Also called Profile Cylinders



Double Cylinder Key & Thumb-turn



Single Cylinder (Also called Half Cylinder) Thumb-turn Only

Material

Solid Brass

Keyway

Schlage C Keyway, 5 Pin. 3 Keys per Cylinder.

Finishes

- · Satin Nickel (US15)
- · Polished Chrome (US26)
- · Oil Rubbed Bronze (US10B)

Cylinder Screw

Each cylinder includes 1 breakable machine screw M5x80mm for fixing cylinder to multipoint lock case with backset up to 2-3/4" (70mm).

Cylinder Thumb-turn




Key Blanks


Key Blanks for Euro Cylinder, Schlage C Keyway, for 5 Pin Cylinder LSK03-55C-NP

Euro-Profile Cylinders for Patio and Entry Function


Total Length: 45mm (10/35) Door Thickness: 1-3/4" (45mm) CYEU-1035TK




Total Length: 50mm (10/40) Door Thickness: 2" (51mm) CYEU-1040TK




Total Length: 55mm (10/45) Door Thickness: 2-1/4" - 2-1/2" (57-63mm) CYEU-1045TK




Total Length: 60mm (10/50) Door Thickness: 2-3/4" – 3" (70 – 76mm) CYEU-1050TK




Total Length: 65mm (10/55) CYEU-1055TK




Total Length: 70mm (35/35) Door Thickness: 1-3/4" (45mm) Lock Case Centered CYEU-3535TK




Total Length: 80mm (40/40) Door Thickness: 2" (51mm) Lock Case Centered CYEU-4040TK




Total Length: 85mm (30/55) Door Thickness: 2-1/4" – 2-1/2" (57 – 63mm) Lock Case Off-Center CYEU-3055TK




Total Length: 85mm (55/30) Door Thickness: 2-1/4" – 2-1/2" (57 – 63mm) Lock Case Off-Center CYEU-5530TK




Total Length: 85mm (35/50) Door Thickness: 2-1/4" – 2-1/2" (57 – 63mm) Lock Case Off-Center CYEU-3550TK



Total Length: 85mm (50/35) Door Thickness: 2-1/4" – 2-1/2" (57 – 63mm) Lock Case Off-Center CYEU-5035TK



Total Length: 90mm (45/45) Door Thickness: 2-1/4" – 2-1/2" (57 – 63mm) Lock Case Centered CYEU-4545TK



Total Length: 100mm (50/50) Door Thickness: 2-3/4" – 3" (70 – 76mm) Lock Case Centered CYEU-5050TK